



Installation Guide

PS•4000 FLAT WALL

SUPPLEMENTAL APPLICATIONS

There are a number of additional tips and techniques available to assist you in the installation of the PolySteel PS•4000 ICF. A few of the topics not covered in this Installation Guide are:

- Cutting Special Angles
- Forming Intersecting Walls
- Transitioning from 8" to 6" Forms
- Panelizing Entire Wall Sections
- Termite Treatments and Applications
- Crawl Space Vents
- Blow Out Repair
- Basement Design
- Brick Ledge Design

For these and other topics of interest, and a more detailed explanation of the topics covered in this Installation Guide, consult your PolySteel Distributor, the PolySteel Installation Manual, or the Prescriptive Method discussed above.

PRODUCT DESCRIPTIONS & ITEM NUMBERS

		<u>Outside Length</u>	<u>Sq. Ft. Outside Wall area</u>	<u>Forms Per Yard of Concrete</u>	<u>Wall Area Per Yard of Concrete</u>	<u>Typical Forms Per Bundle</u>
<u>Half Form 12" High</u>						
PS•4600-1	6" Straight	48"	4.00	13.50	54.00	36
PS•4645-1	6" 45° Corner	18"	1.50	48.70	73.00	72
PS•4690-1	6" 90° Corner	54"	4.50	15.00	67.50	32
PS•4800-1	8" Straight	48"	4.00	10.00	40.00	32
PS•4845-1	8" 45° Corner	20"	1.66	33.50	55.50	72
PS•4890-1	8" 90° Corner	58"	4.83	11.00	53.00	24
<u>Standard Form 24" High</u>						
PS•4600-2	6" Straight	48"	8.00	6.75	54.00	18
PS•4645-2	6" 45° Corner	18"	3.00	24.35	73.00	36
PS•4690-2	6" 90° Corner	54"	9.00	7.50	67.50	16
PS•4800-2	8" Straight	48"	8.00	5.00	40.00	16
PS•4845-2	8" 45° Corner	20"	3.33	16.75	55.50	36
PS•4890-2	8" 90° Corner	58"	9.66	5.50	53.00	12

